

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended). In a radio access control system for a motor vehicle, a method for carrying out simplex transmission of a data message modulated onto a carrier frequency, which comprises:

wirelessly transmitting, in the radio access control system, a data message containing an access code more than one time using at least two different carrier frequencies in temporal succession to increase immunity to interference; and

changing the different carrier frequencies only within one single transmission channel by detuning, with at least one capacitor, an oscillating ~~circuit~~ crystal of a carrier frequency generator.

Claim 2 (original). The method according to claim 1, which further comprises using a different carrier frequency for each of more than two transmissions.

Applic. No. 09/994,197

Response Dated December 14, 2005

Responsive to Office Action of May 13, 2005

Claim 3 (original). The method according to claim 1, which further comprises applying spreading to the data message by a predefined spread sequence.

Claim 4 (original). The method according to claim 3, wherein the at least two different carrier frequencies have a frequency difference in an order of magnitude of a data rate of the data message

Claim 5 (original). The method according to claim 3, wherein the at least two different carrier frequencies have a frequency difference in a range between one quarter and two times a data rate of the data message.

Claim 6 (original). The method according to claim 1, which further comprises applying spreading to the data message by a Direct Sequence Spread Spectrum method.

Claim 7 (original). The method according to claim 6, wherein the at least two different carrier frequencies have a frequency difference in an order of magnitude of a data rate of the data message

Claim 8 (original). The method according to claim 6, wherein the at least two different carrier frequencies have a

Applic. No. 09/994,197

Response Dated December 14, 2005

Responsive to Office Action of May 13, 2005

frequency difference in a range between one quarter and two times a data rate of the data message.

Claim 9 (canceled).

Claim 10 (original). The method according to claim 1, which further comprises setting the at least two different carrier frequencies within a tolerance range of not more than $\pm 10\%$.

Claim 11 (currently amended). In a radio access control system for a motor vehicle, a method for simplex radio transmission in a radio access control system for a motor vehicle, which comprises:

wirelessly transmitting, in the radio access control system, a data message containing an access code more than one time using at least two different carrier frequencies in temporal succession to increase immunity to interference; and

changing the different carrier frequencies only within one single transmission channel by detuning, with at least one capacitor, an oscillating ~~circuit~~ crystal of a carrier frequency generator.

Applic. No. 09/994,197

Response Dated December 14, 2005

Responsive to Office Action of May 13, 2005

Claim 12 (previously presented). In a radio access control system for a motor vehicle, a device for carrying out simplex transmission of a data message modulated onto a carrier frequency, comprising:

a carrier frequency generator for generating different carrier frequencies located only in a single narrowband channel, said carrier frequency generator having at least one capacitor and a detunable oscillator crystal detuned through said at least one capacitor; and

a transmitter modulating data messages containing an access code with said carrier frequencies and wirelessly transmitting the data messages in temporal succession in the radio access control system.

Claim 13 (original). The device according to claim 12, wherein:

said at least one capacitor is a plurality of capacitors; and

a switch respectively connects at least one of said plurality of capacitors to said oscillator crystal to generate different carrier frequencies.

Applic. No. 09/994,197

Response Dated December 14, 2005

Responsive to Office Action of May 13, 2005

Claim 14 (original). The device according to claim 13,
wherein said switch is a program-controlled switch.

Claim 15 (original). The device according to claim 13,
including a carrier frequency control device for setting
different carrier frequencies in a case of multiple
transmission, said control device connected to at least one of
the group consisting of said plurality of capacitors and said
switch.

Claim 16 (previously presented). In a radio access control
system for a motor vehicle, a device for carrying out simplex
transmission of a data message modulated onto a carrier
frequency, comprising:

a carrier frequency generator for generating different carrier
frequencies located only in a single narrowband channel, said
carrier frequency generator having at least one capacitor and
a detunable oscillator crystal detuned through said at least
one capacitor; and

a transmitter modulating data messages containing an access
code with said carrier frequencies and wirelessly transmitting
the data messages more than one time using at least two
different carrier frequencies in temporal succession in the

Applic. No. 09/994,197

Response Dated December 14, 2005

Responsive to Office Action of May 13, 2005

radio access control system to increase immunity to interference; said carrier frequencies only changed to have said carrier frequencies occur within one single transmission channel.

Claim 17 (original). The device according to claim 16, wherein:

said at least one capacitor is a plurality of capacitors; and a switch respectively connects at least one of said plurality of capacitors to said oscillator crystal to generate different carrier frequencies.

Claim 18 (original). The device according to claim 17, wherein said switch is a program-controlled switch.

Claim 19 (original). The device according to claim 17, including a carrier frequency control device for setting different carrier frequencies in a case of multiple transmission, said control device connected to at least one of the group consisting of said plurality of capacitors and said switch.